

Taber's FREEZE PLUG SEAL

APPLICATIONS

- ◆ Freeze Plugs
- ◆ Pipe Threads

ADVANTAGES

- ◆ Saves Time and Money
- ◆ Helps Prevent Leaks
- ◆ Eases Installation
- ◆ Dries Quickly
- ◆ Resists Solvents
- ◆ Not Detrimental to Hot Dip Tanks
- ◆ Cleans up with Soap and Water



ECONOMICAL - Freeze Plug Seal is an economical solution to freeze plug installation problems. It will aid in plug installation and help stop coolant leaks. Includes dauber cap for easy application.

SAFE - Freeze Plug Seal is water based, environmentally and consumer friendly, nonflammable, nonhazardous, and cleans up with soap and warm water before it dries.

TABER'S PRODUCTS, INC.
Email: orders@tabersproducts.com
P.O. Box 197 • 215 Main Street
Henrietta, Missouri 64036
Fax: (816) 494-5485

"It Pays To Stick With Taber's"
1-800-280-9903



FREEZE PLUG SEAL

APPLICATION INSTRUCTIONS

Directions:


- 1) Make sure both freeze plug and hole are clean, dry and free of dirt, rust, oil or dried paints or sealants.
- 2) Apply an even coating as required to plug using dauber. A single coating is sufficient for most applications.
- 3) Drive plug into engine block.
- 4) Wipe excess Freeze Plug Seal from block.

Temperature:

Apply between 40°F and 110°F.

Cleaning:

Cleans up with soap and warm water.



TECHNICAL SPECIFICATIONS

Description:

Taber's Freeze Plug Seal is a water-based, environmentally friendly product formulated to help seal freeze plugs on all types of engines. It also seals pipe threads for light duty. The product is not detrimental to hot dip tanks. Cleans up with soap and warm water before it dries. Nonflammable. Nonhazardous

Physical & Chemical Properties:

Appearance	Creamy gray liquid Black when cured
Odor	Characteristic of Isopropyl Alcohol
Flashpoint	Greater than 300°F
Viscosity	8000-9000 at 30 rpm Brookfield
Specific Gravity	1.4
Weight per Gal.	11.8
pH	9.0 - 9.5

Storage:

Tightly close container. Store in a dry place at a temperature between 40°F and 110°F. Do not allow to freeze. To minimize contamination, do not put unused product back in original container.

Incompatible Materials:

Not to be used with strong oxidizers such as chlorine or pure oxygen.

Health Warning:

Do not ingest. If swallowed consult your physician. Keep out of the reach of children. Contains Isopropyl Alcohol.

For specific information regarding the safe handling and disposal of Taber's Freeze Plug Seal please consult the MSDS, available by calling 1-800-280-9903.