Safety Data Sheet

Issue Date: 20-May-2020 Revision Date: 20-May-2020 Version 1

1. IDENTIFICATION

Product identifier

Product Name Freeze Plug

Other means of identification

SDS # TAB-011

Recommended use of the chemical and restrictions on use

Recommended Use For industrial use.

Details of the supplier of the safety data sheet

Supplier Address Taber's Products, Inc. 215 Main Street Henrietta, MO 64036 Ph: 816-494-5565

Emergency telephone number

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Physical state Liquid

Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Limestone	1317-65-3	10-15
Carbon Black	1333-86-4	1-5
Ethanolamine	141-43-5	0.1-1
Attapulgite Clay	12174-11-7	0.1-1
Glycol Ether EB	111-76-2	0.1-1
2,4,7,9-Tetramethyl-5-Decyne-4,7-Diol	126-86-3	0.1-1
Polyether polyol	9003-11-6	0.1-1
Hydroxyethyl Cellulose	9004-62-0	0.1-1
Quartz	14808-60-7	<0.1
1,2-benzisothiazol-3(2H)-one	2634-33-5	<0.1
Sodium hydroxide	1310-73-2	<0.1

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST AID MEASURES

Description of first aid measures

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes.

Inhalation Remove to fresh air.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms None known.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Not determined.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required.

Environmental precautions

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Materials None

None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Limestone 1317-65-3	-	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 15 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust
Carbon Black 1333-86-4	TWA: 3 mg/m³ inhalable particulate matter	TWA: 3.5 mg/m³ (vacated) TWA: 3.5 mg/m³	IDLH: 1750 mg/m³ TWA: 3.5 mg/m³ TWA: 0.1 mg/m³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Ethanolamine 141-43-5	STEL: 6 ppm TWA: 3 ppm	TWA: 3 ppm TWA: 6 mg/m³ (vacated) TWA: 3 ppm (vacated) TWA: 8 mg/m³ (vacated) STEL: 6 ppm (vacated) STEL: 15 mg/m³	IDLH: 30 ppm TWA: 3 ppm TWA: 8 mg/m ³ STEL: 6 ppm STEL: 15 mg/m ³
Attapulgite Clay 12174-11-7	TWA: 1 mg/m³ respirable particulate matter	-	-
Glycol Ether EB 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³
Quartz 14808-60-7	TWA: 0.025 mg/m³ respirable particulate matter	TWA: 50 μg/m³ TWA: 50 μg/m³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m³ respirable dust: (250)/(%SiO2 + 5) mppcf TWA respirable fraction: (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction	IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust
Sodium hydroxide 1310-73-2	Ceiling: 2 mg/m ³	TWA: 2 mg/m³ (vacated) Ceiling: 2 mg/m³	IDLH: 10 mg/m³ Ceiling: 2 mg/m³

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

AppearanceNot determinedOdorNot determinedColorNot determinedOdor ThresholdNot determined

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH Not determined
Melting point / freezing point
Boiling point / boiling range
Flash point
Evaporation Rate
Flammability (Solid, Gas)
Not determined
Not determined
Not determined
Liquid-Not applicable

Flammability Limit in Air

Upper flammability or explosive Not determined

limits

Lower flammability or explosive Not determined

limits

Vapor Pressure Not determined **Vapor Density** Not determined **Relative Density** Not determined **Water Solubility** Not determined Solubility in other solvents Not determined **Partition Coefficient** Not determined **Autoignition temperature** Not determined **Decomposition temperature** Not determined Kinematic viscosity Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes. **Skin Contact** Avoid contact with skin.

Revision Date: 20-May-2020 TAB-011 - Freeze Plug

Inhalation Do not inhale.

Ingestion Do not ingest.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg(Rabbit)	-
Ethanolamine 141-43-5	= 1720 mg/kg (Rat)	= 1 mL/kg(Rabbit)= 1000 mg/kg (Rabbit)	-
Glycol Ether EB 111-76-2	= 470 mg/kg(Rat)	= 435 mg/kg(Rabbit)	= 486 ppm (Rat) 4 h = 450 ppm (Rat) 4 h
2,4,7,9-Tetramethyl-5-Decyne-4,7- Diol 126-86-3	> 500 mg/kg (Rat)	> 1000 mg/kg(Rabbit)	> 20 mg/L (Rat)1 h
Polyether polyol 9003-11-6	= 5700 mg/kg(Rat)= 16 g/kg(Rat)	-	= 320 mg/m³(Rat) 4 h
1,2-benzisothiazol-3(2H)-one 2634-33-5	= 1020 mg/kg (Rat)	-	-
Sodium hydroxide 1310-73-2	= 325 mg/kg(Rat)	= 1350 mg/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

components are "not classifiable as human carcinogens".

Carbon black is a possible carcinogen when it appears as a respirable dust. Group 3 IARC

Chemical name	ACGIH	IARC	NTP	OSHA
Carbon Black 1333-86-4	A3	Group 2B		X
Glycol Ether EB 111-76-2	A3	Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

Carcinogenicity

A3 - Animal Carcinogen IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

Not determined.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Carbon Black 1333-86-4			5600: 24 h Daphnia magna mg/L EC50
Ethanolamine 141-43-5	15: 72 h Desmodesmus subspicatus mg/L EC50	300 - 1000: 96 h Lepomis macrochirus mg/L LC50 static 227: 96 h Pimephales promelas mg/L LC50 flow-through 200: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 3684: 96 h Brachydanio rerio mg/L LC50 static 114 - 196: 96 h Oncorhynchus mykiss mg/L LC50 static	65: 48 h Daphnia magna mg/L EC50
Glycol Ether EB 111-76-2 Sodium hydroxide		2950: 96 h Lepomis macrochirus mg/L LC50 1490: 96 h Lepomis macrochirus mg/L LC50 static 45.4: 96 h Oncorhynchus mykiss	1000: 48 h Daphnia magna mg/L EC50 1698 - 1940: 24 h Daphnia magna mg/L EC50
1310-73-2		mg/L LC50 static	

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Ethanolamine 141-43-5	-1.91
Glycol Ether EB 111-76-2	0.81
1,2-benzisothiazol-3(2H)-one 2634-33-5	1.3

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Sodium hydroxide	Toxic
1310-73-2	Corrosive

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT Not regulated

IATA Not regulated

<u>IMDG</u> Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
Limestone	Х	ACTIVE	Х	X	Х	Х	Х	Х	Х
Carbon Black	Х	ACTIVE	Х	Х	Х	Х	Х	Х	X
Ethanolamine	Х	ACTIVE	Х	Х	Х	Х	Х	X	Х
Attapulgite Clay	Х		Х			Х		Х	Х
2,4,7,9-Tetramethyl-5- Decyne-4,7-Diol	Х	ACTIVE	Х	Х	Х	Х	Х	Х	Х
Glycol Ether EB	Х	ACTIVE	Х	Х	Х	Х	Х	Х	Х
Polyether polyol	Х	ACTIVE	Х		Х	Х	Х	Х	Х
Hydroxyethyl Cellulose	Х	ACTIVE	Х		Х	Х	Х	Х	Х
Quartz	Х	ACTIVE	Х	Х	Х	Х	Х	Х	X
1,2-benzisothiazol-3(2H)-one	Х	ACTIVE	Х	Х	Х	Х	Х	Х	Х
Sodium hydroxide	Х	ACTIVE	Х	Х	Х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Sodium hydroxide	1000 lb		RQ 1000 lb final RQ
1310-73-2			RQ 454 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium hydroxide	1000 lb			X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Carbon Black - 1333-86-4	Carcinogen
Attapulgite Clay - 12174-11-7	Carcinogen
Quartz - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Limestone 1317-65-3	X	Х	Х
Carbon Black 1333-86-4	Х	Х	Х
Ethanolamine 141-43-5	Х	X	Х
Glycol Ether EB 111-76-2	Х	Х	Х
Quartz 14808-60-7	Х	Х	Х
Sodium hydroxide 1310-73-2	Х	X	Х

16. OTHER INFORMATION

NFPA **Health Hazards Flammability** Instability **Special Hazards** Not determined Not determined Not determined Not determined **HMIS Health Hazards Flammability** Physical hazards **Personal Protection** Not determined Not determined Not determined Not determined

Issue Date:20-May-2020Revision Date:20-May-2020Revision Note:New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet